

CENTRALIZING DYNAMIC TORQUE ANCHOR® EXTRA BY PASS (CTA XB)



The **Centralizing XBDynamic Torque Anchor®** addresses the need for extra bypass required with large volume pumps and horizontal or deviated wells. The extra bypass will allow for more flow area and will avoid sand bridging around the tool.

The running procedures are the same as the Centralizing Dynamic Torque Anchor®

CENTRALIZING XB-DYNAMIC TORQUE ANCHOR® SPECIFICATIONS

Casing OD		Product Number	Tool OD		Tool ID		Tool Length		Connections
inch	mm		inch	mm	inch	mm	inch	mm	inch
4 1/2	114.3	213-10-4523-00	3.63	92.20	2.00	50.8	30.0	762	2 3/8 EU
5 1/2	139.7	213-10-5527-00	4.25	107.95	2.44	62.0	30.0	762	2 7/8 EU
6 5/8	168.3	213-10-6527-00	5.25	133.35	2.44	61.98	30.0	762	2 7/8 EU
6 5/8	168.3	213-10-6535-00	5.25	133.35	3.00	76.2	30.0	762	3 1/2 EU
7	177.8	213-10-7027-00	5.63	143.00	2.44	61.98	30.0	762	2 7/8 EU
7	177.8	213-10-7035-00	5.63	143.00	3.00	76.2	30.0	762	3 1/2 EU
8 5/8	219.1	213-10-8535-00	7.25	184.20	3.00	76.2	32.0	812.8	3 1/2 EU
9 5/8	244.5	213-10-9545-00	8.25	209.60	4.00	101.6	34.0	863.6	4 1/2 EU

* Alternate connections can be provided at customer's request

